MIDDLETON RAILWAY TRUST RISK ASSESSMENT



		ASSESSMENT NO:	E22
ACTIVITY	Jacking of derailed locomotives		
LOCATION	Anywhere		

Tick Boxes Where Applicable

IDENTIFIABLE HAZARDS					
Electrical Noise Moving Parts Heat Fire or explosion Emission Chemical Fall Other (specify)	 ✓ Rotation [From Fluids [Solid [✓ Collapse of support time 	Trapping ✓ From Solid Gas eers	Striking From flame		
PERSONS AT RISK Sole Person ✓ Yersons nearby ✓ Yersons nearby Yersons nearby ✓ Yersons nearby ✓ Yersons Yersons Yersons Yersons Yersons <					
CONTROL MEASURES					
Guards Against Removal of Sources PPE	Clear goggles Dust Mask Other (specify)	Moving parts Welding goggles Gloves ✓	Emissions Ear defenders Helmet 🗸		
Notices	(Specify)				
Required					

ADDITIONAL NOTES

- Jacking of locomotives only to be carried out under supervision of persons experienced in this work.
- Only one end to be jacked at one time.
- Adequate sleeper crib to be erected as jacking proceeds. Support to be under frames where possible.
- All timbers used to be sound and suitable.
- See separate instructions on this.

ASSESSMENT CARRIED OUT BY:	S J Roberts
DATE:	26/1/01
REVIEWED:	01/03/15